



SimpleSpec 500.03

Lightbox Shelving

Introduction LT Series

- . LED Life of approximately 50K hours, under normal operating conditions
- . Low wattage, low heat, low voltage (24VDC Operation)
- . Design prevents “scalloping” effect, providing consistent and uniform illumination
- . Emits no UV or infrared light and does not contain lead, mercury, or glass, allowing for Eco-friendly handling and disposal when required
- . Simple user friendly installation
- . UL/cUL 2108 and CE Listed
- . 4 inch joinable segments; can be cut to 4 inch segments




Table of Contents

1 Specifications

2 Wiring Installation Diagrams

2 Wiring Diagram

3 0-10V Dimming $\leq 100W$

4 0-10V Dimming 100W-1200W


5 Dimensions

5 3-60-765 - Dimmable Power Supply

Specifications

LEDs

Part Number	LED Bar Color	Volts	Power (W/ft)	Max Feet per 100W PS	Color Temperature
3-60-766	Warm White	24	1.44	100'	2700K
3-60-767	Warm White	24	1.44	100'	3000K
3-60-768	Natural White	24	1.44	100'	4000K
3-60-769	Cool White	24	1.44	100'	6300K
3-60-770	Red	12	2.88	16'	Red
3-60-771	Green	12	2.88	16'	Green
3-60-772	Blue	12	2.88	16'	Blue



Drivers

Part Number	Description	Dimensions	Input Voltage	Input Current	Output Power	Output Voltage	Output Current
3-60-497	0-10V Slide Control Wall Dimmer	-	-	-	-	-	-
3-60-765	96W Dimmable Power Supply	11.7"×2.36"×1.4"	120-277VAC	.8/.35	96	24	4




3-60-497 Slide Control




3-60-765 Dimmable Power Supply

Installation
Wiring Diagram




Installation

Wiring Diagram - 0-10V Dimming ≤100W



Installation

Wiring Diagram - 0-10V Dimming 100W-1200W



Dimensions

3-60-765 - Dimmable Power Supply

